


VubaMac Base Build Up


Vehicle

Vehicle Load Bearing Environmentally Friendly “No Dig” Base, Formulated and Patented to Create a Highly Strong Monolithic Resin Surface.

Our VubaMac is made up of 4 different layers to create an environmentally friendly “No Dig” base suitable for both vehicle and pedestrian traffic. Using Vuba’s SRM (Structural Reinforcement Mesh), a NON UV Recycled Railway Ballast and traditional Vuba Resin Bound Surfacing as the surface course. The product allows for Resin Bound Surfacing to be laid onto an MOT base rather than traditional methods of using Asphalt or Concrete for example. VubaMac is also SUDS compliant and suitable for Tree Root Protection Areas.



1. **Resin Bound Surfacing** spread using a spazzle or sledge, and finished using a steel trowel or power trowel. / 18mm
2. **Structural Reinforcement Mesh (SRM) Top Layer.** ←
3. **Urethane Binder Course** is a layer comprised of mixed Recycled Railway Ballast and VubaMac Binder spread with a spazzle and finished using a wetpour roller. / 30mm
4. **SRM Base Layer.** ←
5. **Granolithic Dust** binds together to form a → very strong laying course and helps to ensure a flat smooth surface for the SRM.
6. **Sub-Base** a 175mm depth of well compacted, non-frost susceptible Type 3 granular sub-base to SHW clause 805 or locally available secondary or recycled aggregates which comply with the requirements of the specifications for Highway Works for sub-bases. The sub-base ought to be installed in layers (2 to 3), ensuring that each layer is fully compacted.




Vehicle Traffic



1 Day Application



No Dig



Long Term Flexural Resistance



Green Recycled



Find out more **from our technical team:**

Milly Sheffield | Technical, Research and Development

+44 (0) 7940 295105

milly.sheffield@vubagroup.com

vubaresinproducts.com